

SPANNINGSTABEL TWO WHEEL TYRES

CONTROLEER REGELMATIG UW BANDENSPIJNING.

EEN BAND BEREDEN OP DE JUISTE BANDENSPIJNING:

- LOOPT LICHTER
- HEEFT MINDER KANS OP LEKRIJDEN
- GAAT LANGER MEE
- GEEFT OPTIMAAL COMFORT

TOUR/TREK/CITY/MTB

Inch	ETRTO	Inchmaat	Bandenspanning min./max.
12"	62-203	12.1/2x2.1/4	2.0-4.0
16"	47-305	16x1.75	2.8-4.5
18"	47-355	18x1.75	2.8-4.5
	37-387	18x1.3/8	3.8-5.5
20"	35-406	20x1.30	3.8-5.5
	47-406	20x1.75	2.8-4.5
	50-406	20x2.00	2.5-4.5
	54-406	20x2.10	2.0-4.0
	57-406	20x2.25	2.0-4.0
	37-438	20x1.3/8	3.8-5.5
22"	47-457	22x1.75	2.8-4.5
	37-489	22x1.3/8	3.8-5.5
24"	47-507	24x1.75	2.8-4.5
	50-507	24x2.00	2.5-4.5
	37-540	24x1.3/8	3.8-5.5
26"	40-559	26x1.50	3.5-5.0
	44-559	26x1.70	2.8-4.5
	50-559	26x1.90	2.5-4.5
	54-559	26x2.10	2.0-4.0
	57-559	26x2.25	2.0-4.0
	60-559	26x2.35	2.0-4.0
	47-571	26x2.00	2.8-4.5
	37-584	26x1.1/2x1.3/8	3.8-5.5
	37-590	26x1.3/8	3.8-5.5
	40-590	26x1.3/8x1.1/2	3.5-5.0
	47-590	26x1.5/8	3.5-5.0
28"	28-622	28x1.5/8x1.1/8	4.5-6.5
	30-622	700x32C	4.0-6.0
	32-622	28x1.5/8x1.1/4	4.0-6.0
	34-622	700x34C	4.0-6.0
	37-622	28x1.5/8x1.3/8	3.8-5.5
	40-622	28x1.5/8x1.1/2	3.5-5.0
	42-622	28x1.60	3.5-5.0
	47-622	28x1.75	2.8-4.5
	50-622	28x2.00	2.5-4.5
	54-622	28x2.10	2.0-4.0
	60-622	28x2.35	2.0-4.0
	40-635	28x1.1/2	3.5-5.0

SCOOTER/MOPED

ETRTO	Vorgestreven bandenspanning
100/90-10	2.50
120/70-12	2.80
130/70-12	2.80
130/60-13	2.30
3.50-10	3.25
120/90-10	2.50
130/90-10	1.75
100/80-10	3.00
140/60-13	2.30
140/70-12	2.80
110/90-12	2.50
110/80-10	2.50
130/70-13	2.80
110/90-13	2.30

RACE

Voor racebanden gelden andere bandenspanningsnormen.
Deze zijn te vinden bij de portierstolpe.